

Frequency Domain System Identification Toolbox

Usage and Examples

Hints for First-Time Users

I. Using the Graphical User Interface:

Type `fdtool` to start.

In the main window of the GUI, extensive helps are available, covering general use, load/save data, etc.

- Help mechanisms:
 - tooltipstrings in every subwindow: when the mouse is moved above a control object, small "balloon helps" pop up with a short information text. Note: the main window contains so-called patches which do not have tooltipstrings.
 - There is a Help menu in every window. Under this, there is a special submenu, 'Help on Object': the selected object will be explained in a separate window
- How to run demonstrations: In the main window select Help / Introductory Demos (or Complex Examples and Demos), then select the desired one from the window. Recommended demos:
 - Introductory Demos / To GUI /
 - Helps: Some introduction to the help facilities
 - Creating data objects: Examples to generate and import data objects
 - Processing time domain data: A simple series of steps
 - Complex Examples and Demos
 - Bandpass filter %Quick processing of freq. domain data
 - Electrical machine %Processing data from a wide frequency band
 - Wilkinson-type system %Processing a badly conditioned system, using orthogonal polynomials
- Record and replay your GUI actions: select the menu Recorder / Open, push Record on the recorder, now use the GUI, then press stop. Save the sequence of actions if you want. Replay: rewind recorder to Action 1, then press PLAY.

II. Command-line toolbox

- Load sample objects to workspace:
 - `load robotarm %load sample data`
 - `load rarmmods %load sample models`
- Utilities: `plot(m)`, `plot(f)`, `plot(robotarm_6models)`, `bode(m)`, `nyquist(m)`, `diff(robotarm_6models{1},m)`
- Preprocess data, e.g. remove the effect of a known parametric model: `f/m`
- Illustrate uncertainty of identified model: `cloud(m)`, `zoom on`, and then zoom-in around

the right valley of the transfer function to see the different transfer functions

- Combine models (series connection of systems): `m*m`
- Convert models to/from the Control System Toolbox objects: `ss(m)`, `tf(m)`, `zpk(m)`
`fidmodel(tf(m))`
- Information on objects (tiddata, fiddata, fidmodel), e.g.:
 - `help fiddata` %help on creator
 - `help(fiddata)` %description of object
 - `helpc(fiddata)` %contents of class directory
- Information on new call: `help elis`, `help simfou`, `help eliscost`, etc.
- Help on earlier (more complicated) syntax: `oldhelp simfou`, `oldhelp elis`, etc.
- List possible call forms: `usage simfou` (the command `usage` also works for other MATLAB functions in general)

III. Self-tests

- Test to make sure that no name clash happens with function M-files on the MATLAB path: run `fdunique`
- General test of the whole GUI: simply call `fdguitst`, and let it run untouched for about an hour

[Back to the Developers' page](http://elecwww.vub.ac.be/fdident/usage.html)