

# **QNX<sup>®</sup> Neutrino<sup>®</sup> RTOS**

---

## **Multicore Processing**

### ***User's Guide***

*For QNX<sup>®</sup> Neutrino<sup>®</sup> 6.4.1*

© 2006–2009, QNX Software Systems GmbH & Co. KG. All rights reserved.

Published under license by:

**QNX Software Systems International Corporation**

175 Terence Matthews Crescent

Kanata, Ontario

K2M 1W8

Canada

Voice: +1 613 591-0931

Fax: +1 613 591-3579

Email: [info@qnx.com](mailto:info@qnx.com)

Web: <http://www.qnx.com/>

Electronic edition published 2009

QNX, Neutrino, Photon, Photon microGUI, Momentics, and Aviage are trademarks, registered in certain jurisdictions, of QNX Software Systems GmbH & Co. KG. and are used under license by QNX Software Systems International Corporation. All other trademarks belong to their respective owners.

<b>About This Guide</b>	<b>v</b>
What you'll find in this guide	vii
Typographical conventions	vii
Note to Windows users	viii
Technical support	viii
<b>1 What is Multicore Processing?</b>	<b>1</b>
<b>2 A Quick Introduction to Multicore Processing</b>	<b>5</b>
Setting up the OS image	7
Trying symmetric multiprocessing	8
Trying bound multiprocessing	8
<b>3 Developing Multicore Systems</b>	<b>11</b>
Building a multicore image	13
The impact of multicore	13
To multicore or not to multicore	13
Thread affinity	14
Multicore and synchronization primitives	16
Multicore and FIFO scheduling	16
Multicore and interrupts	17
Multicore and atomic operations	17
Adaptive partitioning	18
Designing with multiprocessing in mind	18
Use the multicore primitives	18
Assume that threads <i>really do</i> run concurrently	18
Break the problem down	18
<b>Glossary</b>	<b>21</b>
<b>Index</b>	<b>25</b>



## ***About This Guide***

---



## What you'll find in this guide

The Multicore Processing *User's Guide* describes how you can use symmetric multiprocessing to get the most performance possible out of a multiprocessor system. It also describes how to use bound multiprocessing to restrict which processors a thread can run on.

The following table may help you find information quickly in this guide:

For information on:	Go to:
Multicore processing in general	What is Multicore Processing?
Getting started with multicore processing	A Quick Introduction to Multicore Processing
Programming with multicore processing in mind	Developing Multicore Systems
Terminology used in this guide	Glossary

## Typographical conventions

Throughout this manual, we use certain typographical conventions to distinguish technical terms. In general, the conventions we use conform to those found in IEEE POSIX publications. The following table summarizes our conventions:

Reference	Example
Code examples	<code>if( stream == NULL )</code>
Command options	<code>-lR</code>
Commands	<code>make</code>
Environment variables	<code>PATH</code>
File and pathnames	<code>/dev/null</code>
Function names	<code>exit()</code>
Keyboard chords	Ctrl-Alt-Delete
Keyboard input	<code>something you type</code>
Keyboard keys	Enter
Program output	<code>login:</code>
Programming constants	<code>NULL</code>

*continued...*

Reference	Example
Programming data types	<code>unsigned short</code>
Programming literals	<code>0xFF, "message string"</code>
Variable names	<code>stdin</code>
User-interface components	<b>Cancel</b>

We use an arrow (→) in directions for accessing menu items, like this:

You'll find the **Other...** menu item under **Perspective→Show View**.

We use notes, cautions, and warnings to highlight important messages:



Notes point out something important or useful.



**CAUTION:** Cautions tell you about commands or procedures that may have unwanted or undesirable side effects.



**WARNING:** Warnings tell you about commands or procedures that could be dangerous to your files, your hardware, or even yourself.

## Note to Windows users

In our documentation, we use a forward slash (/) as a delimiter in *all* pathnames, including those pointing to Windows files.

We also generally follow POSIX/UNIX filesystem conventions.

## Technical support

To obtain technical support for any QNX product, visit the **Support + Services** area on our website ([www.qnx.com](http://www.qnx.com)). You'll find a wide range of support options, including community forums.



# **What is Multicore Processing?**



Multiprocessing systems, whether discrete or multicore, can greatly improve your applications' performance. As described in the Multicore Processing chapter of the *System Architecture* guide, there's a multiprocessor version of Neutrino that runs on:

- Pentium-based multiprocessor systems that conform to the Intel MultiProcessor Specification (MP Spec)
- MIPS-based systems
- PowerPC-based systems

If you have one of these systems, then you're probably itching to try it out, but are wondering what you have to do to get Neutrino running on it. Well, the answer is not much. The only part of Neutrino that's different for a multiprocessor system is the microkernel — another example of the advantages of a microkernel architecture!



---

To determine how many processors there are on your system, look at the `num_cpu` entry of the system page. For more information, see “Structure of the system page” in the Customizing Image Startup Programs chapter of *Building Embedded Systems*.

---

Neutrino supports these operating modes for multiprocessing:

#### Asymmetric multiprocessing (AMP)

A separate OS, or a separate instantiation of the same OS, runs on each CPU.

#### Symmetric multiprocessing (SMP)

A single instantiation of an OS manages all CPUs simultaneously, and applications can float to any of them.

#### Bound multiprocessing (BMP)

A single instantiation of an OS manages all CPUs simultaneously, but you can lock individual applications or threads to a specific CPU.

SMP lets you get the most performance out of your system, but you might need to use BMP for the few applications that may not work under SMP, or if you want to explicitly control the process-level distribution of CPU usage.



## ***Chapter 2***

---

# **A Quick Introduction to Multicore Processing**

### ***In this chapter...***

Setting up the OS image	7
Trying symmetric multiprocessing	8
Trying bound multiprocessing	8



This chapter gives you a quick hands-on introduction to multicore processing. The main steps are as follows:

- Setting up the OS image
- Trying symmetric multiprocessing
- Trying bound multiprocessing

## Setting up the OS image

- 1 Log in as **root**.
- 2 Go to the directory that holds the buildfile for your system's boot image (e.g. `/boot/build`).
- 3 Create a copy of the buildfile:  

```
cp qnxbasedma.build qnxbasedma_multicore.build
```
- 4 Edit the copy (e.g. `qnxbasedma_multicore.build`).
- 5 Search for **procnto**. The line might look like this:

```
PATH=/proc/boot:/bin:/usr/bin:/opt/bin \
LD_LIBRARY_PATH=/proc/boot:/lib:/usr/lib:/lib/dll:/opt/lib \
procnto-instr
```




---

In a real buildfile, you can't use a backslash (\) to break a long line into shorter pieces, but we've done that here, just to make the command easier to read.

---

- 6 Change **procnto** to the appropriate multicore version; see `/proc/boot` to see which uniprocessor version you're using, and then add **-smp** to it. For more information, see **procnto** in the *Utilities Reference*. For example:

```
PATH=/proc/boot:/bin:/usr/bin:/opt/bin \
LD_LIBRARY_PATH=/proc/boot:/lib:/usr/lib:/lib/dll:/opt/lib \
procnto-smp-instr
```




---

Although the multiprocessing version of **procnto** has "SMP" in its name, it also supports BMP. You can even use bound and symmetric multiprocessing simultaneously on the same system.

---

- 7 Save your changes to the buildfile.
- 8 Generate a new boot image:  

```
mkifs qnxbasedma_multicore.build qnxbasedma_multicore.ifs
```
- 9 Put the new image in place. In order to ensure you can still boot your system if an error occurs, we recommend the following:

- If you're using the Power-Safe filesystem (**fs-qnx6.so**), add your image to the ones in **/.boot/** instead of overwriting an existing image.
- If you're using the QNX 4 filesystem (**fs-qnx4.so**), copy your current boot image to **/.altboot** by doing the following:

```
cp /.altboot /old_altboot
cp /.boot /.altboot
cp apsdma.ifs /.boot
```

- 10 Reboot your system.

## Trying symmetric multiprocessing

- 1 Log in as a normal user.
- 2 Start some processes that run indefinitely. For example, use the **hogs** utility to display which processes are using the most CPU:

```
hogs -n -%10
```

- 3 Use **pidin sched** to see which processor your processes are running on. If you're using the IDE, you can use the System Information perspective to watch the threads migrate.
- 4 Create a program called **greedy.c** that simply loops forever:

```
#include <stdlib.h>

int main( void )
{
    while (1) {
    }

    return EXIT_SUCCESS;
}
```

- 5 Compile it, and then run it:

```
gcc -o greedy greedy.c
./greedy &
```

On a uniprocessor system, this would consume all the processing time (unless you're using adaptive partitioning). On a multicore system, it consumes all the time on one processor.

- 6 Use **pidin sched** to see which processor your other processes are running on. They're likely running on different processors from **greedy**.

## Trying bound multiprocessing

- 1 Use the **-C** or **-R** option (or both) to the **on** utility to start a shell on a specific set of processors:



```
on -C 0 ksh
```

- 2** Start some new processes from this shell. Note that they run only on the first processor.
- 3** Use the **-C** or **-R** option (or both) to **slay** to change the runmask for one of these processes. Note that the process runs only on the processors that you just specified, while any children run on the processors you specified for the shell.
- 4** Use the **-C** or **-R** option (or both) *and* the **-i** option to **slay** to change the runmask and inherit mask for one of these processes. Note that the process and its children run only on the newly specified processors.



# **Developing Multicore Systems**

### ***In this chapter...***

Building a multicore image	13
The impact of multicore	13
Designing with multiprocessing in mind	18



## Building a multicore image

Assuming you're already familiar with building a bootable image for a single-processor system (as described in the Making an OS Image chapter in *Building Embedded Systems*), let's look at what you have to change in the buildfile for a multicore system.

As we mentioned earlier, basically all you need to use is the multicore kernel (**procnto-smp**) when building the image.

Here's an example of a buildfile:

```
#   A simple multicore buildfile

[virtual=x86,bios] .bootstrap = {
    startup-bios
    PATH=/proc/boot procnto-smp
}
[+script] .script = {
    devc-con -e &
    reopen /dev/con1
    [+session] PATH=/proc/boot esh &
}

libc.so
[type=link] /usr/lib/ldqnx.so.2=/proc/boot/libc.so

[data=copy]
devc-con
esh
ls
```

After building the image, you proceed in the same way as you would with a single-processor system.

## The impact of multicore

Although the actual changes to the way you set up the processor to run SMP are fairly minor, the *fact* that you're running on a multicore system can have a major impact on your software!

The main thing to keep in mind is this: in a single processor environment, it may be a nice “design abstraction” to pretend that threads execute in parallel; under a multicore system, they *really do* execute in parallel! (With BMP, you can make your threads run on a specific CPU.)

In this section, we'll examine the impact of multicore on your system design.

### To multicore or not to multicore

It's possible to use the non-multicore kernel on a multicore box. In this case, only processor 0 will be used; the other processors won't run your code. This is a waste of additional processors, of course, but it does mean that you *can* run images from single-processor boxes on an multicore box. (You can also run SMP-ready images on single-processor boxes.)

It's also possible to run the multicore kernel on a uniprocessor system, but it requires a 486 or higher on x86 architectures, and a multicore-capable implementation on MIPS and PPC.

## Thread affinity

One issue that often arises in a multicore environment can be put like this: “Can I make it so that one processor handles the GUI, another handles the database, and the other two handle the realtime functions?”

The answer is: “Yes, absolutely.”

This is done through the magic of *thread affinity*, the ability to associate certain programs (or even threads within programs) with a particular processor or processors.

Thread affinity works like this. When a thread starts up, its affinity mask (or runmask) is set to allow it to run on all processors. This implies that there's *no* inheritance of the thread affinity mask, so it's up to the thread to use *ThreadCtl()* with the `_NTO_TCTL_RUNMASK` control flag to set its runmask:

```
if (ThreadCtl( _NTO_TCTL_RUNMASK, (void *)my_runmask) == -1) {
    /* An error occurred. */
}
```

The runmask is simply a bitmap; each bit position indicates a particular processor. For example, the runmask `0x05` (binary `00000101`) allows the thread to run on processors 0 (the `0x01` bit) and 2 (the `0x04` bit).



If you use `_NTO_TCTL_RUNMASK`, the runmask is limited to the size of an `int` (currently 32 bits). Threads created by the calling thread don't inherit the specified runmask.

If you want to support more processors than will fit in an `int`, or you want to set the inherit mask, you'll need to use the `_NTO_TCTL_RUNMASK_GET_AND_SET_INHERIT` command described below.

The `<sys/neutrino.h>` file defines some macros that you can use to work with a runmask:

*RMSK\_SET(cpu, p)*

Set the bit for *cpu* in the mask pointed to by *p*.

*RMSK\_CLR(cpu, p)*

Clear the bit for *cpu* in the mask pointed to by *p*.

*RMSK\_ISSET(cpu, p)*

Determine if the bit for *cpu* is set in the mask pointed to by *p*.

The CPUs are numbered from 0. These macros work with runmasks of any length.

Bound multiprocessing (BMP) is a variation on SMP that lets you specify which processors a process or thread *and its children* can run on. To specify this, you use an *inherit mask*.

To set a thread's inherit mask, you use *ThreadCtl()* with the `_NTO_TCTL_RUNMASK_GET_AND_SET_INHERIT` control flag. Conceptually, the structure that you pass with this command is as follows:

```
struct _thread_runmask {
    int size;
    unsigned runmask[size];
    unsigned inherit_mask[size];
};
```

If you set the *runmask* member to a nonzero value, *ThreadCtl()* sets the runmask of the calling thread to the specified value. If you set the *runmask* member to zero, the runmask of the calling thread isn't altered.

If you set the *inherit\_mask* member to a nonzero value, *ThreadCtl()* sets the calling thread's inheritance mask to the specified value(s); if the calling thread creates any children by calling *pthread\_create()*, *fork()*, *spawn()*, *vfork()*, and *exec()*, the children inherit this mask. If you set the *inherit\_mask* member to zero, the calling thread's inheritance mask isn't changed.

If you look at the definition of `_thread_runmask` in `<sys/neutrino.h>`, you'll see that it's actually declared like this:

```
struct _thread_runmask {
    int size;
    /* unsigned runmask[size]; */
    /* unsigned inherit_mask[size]; */
};
```

This is because the number of elements in the *runmask* and *inherit\_mask* arrays depends on the number of processors in your multicore system. You can use the *RMSK\_SIZE()* macro to determine how many unsigned integers you need for the masks; pass the number of CPUs (found in the system page) to this macro.

Here's a code snippet that shows how to set up the runmask and inherit mask:

```
unsigned    num_elements = 0;
int         *rsizep, masksize_bytes, size;
unsigned    *rmaskp, *imaskp;
void        *my_data;

/* Determine the number of array elements required to hold
 * the runmasks, based on the number of CPUs in the system. */
num_elements = RMSK_SIZE(_syspage_ptr->num_cpu);

/* Determine the size of the runmask, in bytes. */
masksize_bytes = num_elements * sizeof(unsigned);

/* Allocate memory for the data structure that we'll pass
 * to ThreadCtl(). We need space for an integer (the number
 * of elements in each mask array) and the two masks
 * (runmask and inherit mask). */

size = sizeof(int) + 2 * masksize_bytes;
```

```

if ((my_data = malloc(size)) == NULL) {
    /* Not enough memory. */
    :
} else {
    memset(my_data, 0x00, size);

    /* Set up pointers to the "members" of the structure. */
    rsizep = (int *)my_data;
    rmaskp = rsizep + 1;
    imaskp = rmaskp + num_elements;

    /* Set the size. */
    *rsizep = num_elements;

    /* Set the runmask. Call this macro once for each processor
       the thread can run on. */
    RMSK_SET(cpu1, rmaskp);

    /* Set the inherit mask. Call this macro once for each
       processor the thread's children can run on. */
    RMSK_SET(cpu1, imaskp);

    if ( ThreadCtl( _NTO_TCTL_RUNMASK_GET_AND_SET_INHERIT,
                    my_data) == -1) {
        /* Something went wrong. */
        :
    }
}

```

You can also use the **-C** and **-R** options to the **on** command to launch processes with a runmask (assuming they don't set their runmasks programmatically); for example, use **on -C 1 io-pkt-v4** to start **io-pkt-v4** and lock all threads to CPU 1. This command sets both the runmask and the inherit mask.

You can also use the same options to the **slay** command to modify the runmask of a running process or thread. For example, **slay -C 0 io-pkt-v4** moves all of **io-pkt-v4**'s threads to run on CPU 0. If you use the **-C** and **-R** options, **slay** sets the runmask; if you also use the **-i** option, **slay** also sets the process's or thread's inherit mask to be the same as the runmask.

## Multicore and synchronization primitives

Standard synchronization primitives (barriers, mutexes, condvars, semaphores, and all of their derivatives, e.g. sleep-on locks) are safe to use on a multicore box. You don't have to do anything special here.

## Multicore and FIFO scheduling

A common single-processor "trick" for coordinated access to a shared memory region is to use FIFO scheduling between two threads running at the same priority. The idea is that one thread will access the region and then call *SchedYield()* to give up its use of the processor. Then, the second thread would run and access the region. When it was done, the second thread too would call *SchedYield()*, and the first thread would run again. Since there's only one processor, both threads would cooperatively share that processor.



This FIFO trick won't work on an SMP system, because *both* threads may run simultaneously on different processors. You'll have to use the more "proper" thread synchronization primitives (e.g. a mutex), or use BMP to tie the threads to specific CPUs.

## Multicore and interrupts

The following method is closely related to the FIFO scheduling trick. On a single-processor system, a thread and an interrupt service routine are mutually exclusive, because the ISR runs at a higher priority than any thread. Therefore, the ISR can preempt the thread, but the thread can *never* preempt the ISR. So the only "protection" required is for the thread to indicate that during a particular section of code (the *critical section*) interrupts should be disabled.

Obviously, this scheme breaks down in a multicore system, because again the thread and the ISR could be running on different processors.

The solution in this case is to use the *InterruptLock()* and *InterruptUnlock()* calls to ensure that the ISR won't preempt the thread at an unexpected point. But what if the thread preempts the ISR? The solution is the same: use *InterruptLock()* and *InterruptUnlock()* in the ISR as well.




---

We recommend that you *always* use *InterruptLock()* and *InterruptUnlock()*, both in the thread and in the ISR. The small amount of extra overhead on a single-processor box is negligible.

---

## Multicore and atomic operations

Note that if you wish to perform simple atomic operations, such as adding a value to a memory location, it isn't necessary to turn off interrupts to ensure that the operation won't be preempted. Instead, use the functions provided in the C include file `<atomic.h>`, which let you perform the following operations with memory locations in an atomic manner:

Function	Operation
<i>atomic_add()</i>	Add a number
<i>atomic_add_value()</i>	Add a number and return the original value of <i>*loc</i>
<i>atomic_clr()</i>	Clear bits
<i>atomic_clr_value()</i>	Clear bits and return the original value of <i>*loc</i>
<i>atomic_set()</i>	Set bits
<i>atomic_set_value()</i>	Set bits and return the original value of <i>*loc</i>

*continued...*

Function	Operation
<code>atomic_sub()</code>	Subtract a number
<code>atomic_sub_value()</code>	Subtract a number and return the original value of <i>*loc</i>
<code>atomic_toggle()</code>	Toggle (complement) bits
<code>atomic_toggle_value()</code>	Toggle (complement) bits and return the original value of <i>*loc</i>



The `*_value()` functions may be slower on some systems (e.g. 386), so don't use them unless you really want the return value.

## Adaptive partitioning

You can use adaptive partitioning on a multicore system, but there are some interactions to watch out for. For more information, see “Using adaptive partitioning and multicore together” in the Adaptive Partitioning Scheduling Details chapter of the Adaptive Partitioning *User's Guide*.

## Designing with multiprocessing in mind

You may not have a multicore system today, but wouldn't it be great if your software just ran faster on one when you or your customer upgrade the hardware?

While the general topic of how to design programs so that they can scale to *N* processors is still the topic of research, this section contains some general tips.

### Use the multicore primitives

Don't assume that your program will run only on one processor. This means staying away from the FIFO synchronization trick mentioned above. Also, you should use the multicore-aware `InterruptLock()` and `InterruptUnlock()` functions.

By doing this, you'll be “multicore-ready” with little negative impact on a single-processor system.

### Assume that threads *really do* run concurrently

As mentioned above, it isn't merely a useful “programming abstraction” to pretend that threads run simultaneously; you should design as if they really do. That way, when you move to a multicore system, you won't have any nasty surprises (but you can use BMP if you have problems and don't want to modify the code).

### Break the problem down

Most problems can be broken down into independent, parallel tasks. Some are easy to break down, some are hard, and some are impossible. Generally, you want to look at the data flow going through a particular problem. If the data flows are *independent*

(i.e. one flow doesn't rely on the results of another), this can be a good candidate for parallelization within the process by starting multiple threads. Consider the following graphics program snippet:

```
do_graphics ()
{
    int    x;

    for (x = 0; x < XRESOLUTION; x++) {
        do_one_line (x);
    }
}
```

In the above example, we're doing ray-tracing. We've looked at the problem and decided that the function *do\_one\_line()* only generates output to the screen — it doesn't rely on the results from any other invocation of *do\_one\_line()*.

To make optimal use of a multicore system, you would start multiple threads, each running on one processor.

The question then becomes how many threads to start. Obviously, starting XRESOLUTION threads (where XRESOLUTION is far greater than the number of processors, perhaps 1024 to 4) isn't a particularly good idea — you're creating a lot of threads, all of which will consume stack resources and kernel resources as they compete for the limited pool of CPUs.

A simple solution would be to find out the number of CPUs that you have available to you (via the system page pointer) and divide the work up that way:

```
#include <sys/syspage.h>

int    num_x_per_cpu;

do_graphics ()
{
    int    num_cpus;
    int    i;
    pthread_t *tids;

    // figure out how many CPUs there are...
    num_cpus = _syspage_ptr -> num_cpu;

    // allocate storage for the thread IDs
    tids = malloc (num_cpus * sizeof (pthread_t));

    // figure out how many X lines each CPU can do
    num_x_per_cpu = XRESOLUTION / num_cpus;

    // start up one thread per CPU, passing it the ID
    for (i = 0; i < num_cpus; i++) {
        pthread_create (&tids[i], NULL, do_lines, (void *) i);
    }

    // now all the "do_lines" are off running on the processors

    // we need to wait for their termination
    for (i = 0; i < num_cpus; i++) {
        pthread_join (tids[i], NULL);
    }
}
```

```
        // now they are all done
    }

    void *
    do_lines (void *arg)
    {
        int    cpunum = (int) arg; // convert void * to an integer
        int    x;

        for (x = cpunum * num_x_per_cpu; x < (cpunum + 1) *
             num_x_per_cpu; x++) { do_line (x);
        }
    }
}
```

The above approach lets the maximum number of threads run simultaneously on the multicore system. There's no point creating more threads than there are CPUs, because they'll simply compete with each other for CPU time.

Note that in this example, we didn't specify which processor to run each thread on. We don't need to in this case, because the READY thread with the highest priority always runs on the next available processor. The threads will tend to run on different processors (depending on what else is running in the system). You typically use the same priority for all the worker threads if they're doing similar work.

An alternative approach is to use a semaphore. You could preload the semaphore with the count of available CPUs. Then, you create threads whenever the semaphore indicates that a CPU is available. This is conceptually simpler, but involves the overhead of creating and destroying threads for each iteration.

## ***Glossary***

---



### **asymmetric multiprocessing (AMP)**

A separate OS, or a separate instantiation of the same OS, runs on each CPU.

### **bound multiprocessing (BMP)**

A single instantiation of an OS manages all CPUs simultaneously, but you can lock individual applications or threads to a specific CPU.

### **discrete (or traditional) multiprocessor system**

A system that has separate physical processors hooked up in multiprocessing mode over a board-level bus.

### **hard thread affinity**

A user-specified binding of a thread to a set of processors, done by means of a **runmask**. Contrast **soft thread affinity**.

### **inherit mask**

A bitmask that specifies which processors a thread's children can run on. Contrast **runmask**.

### **multicore system**

A chip that has one physical processor with multiple CPUs interconnected over a chip-level bus.

### **runmask**

A bitmask that indicates which processors a thread can run on. Contrast **inherit mask**.

### **soft thread affinity**

The scheme whereby the microkernel tries to dispatch a thread to the processor where it last ran, in an attempt to reduce thread migration from one processor to another, which can affect cache performance. Contrast **hard thread affinity**.

### **symmetric multiprocessing (SMP)**

A single instantiation of an OS manages all CPUs simultaneously, and applications can float to any of them.





## !

`_NTO_TCTL_RUNMASK` 14  
`_NTO_TCTL_RUNMASK_GET_AND_SET_INHERIT` 15  
`_thread_runmask` 15

## A

affinity, thread 14  
AMP (Asymmetric Multiprocessing) 3  
atomic operations 17

## B

BMP (Bound Multiprocessing) 3, 14  
    trying it 8  
buildfiles  
    modifying for multicore processing 7  
    sample 13

## C

conventions  
    typographical vii  
CPUs, number of 19

## F

FIFO scheduling, using with multicore 16

## I

images, building for multicore 13  
inherit mask 14  
*InterruptLock()* 17, 18  
interrupts, handling 17  
*InterruptUnlock()* 17, 18  
ISR, preemption considerations 17

## M

multicore processing 3  
    building an image for 13  
    designing for 18  
    interrupts and 17  
    sample buildfile for 13  
mutexes 16

## O

`on` utility 8, 16  
operations, atomic 17  
OS images, building for multicore 7, 13

## P

pathname delimiter in QNX Momentics  
    documentation viii  
`pidin` 8  
processes, processor running on

- displaying 8
- specifying 9
- processors, determining number of 3
- procnto\*-smp** 7, 13

## R

- RMSK\_CLR()* 14
- RMSK\_ISSET()* 14
- RMSK\_SET()* 14
- RMSK\_SIZE()* 15
- runmask 14

## S

- scheduling algorithms, using FIFO with
  - multicore 16
- SchedYield()*, using with multicore 16
- slay** 9, 16
- SMP (Symmetric Multiprocessing) 3
  - trying it 8
- synchronization primitives and multicore 16
- system page, number of CPUs 19

## T

- tasks, parallel 18
- thread affinity 14
- ThreadCtl()* 14, 15
- threads, running concurrently 13, 18
- typographical conventions vii